

INFORMATION

Dampier to Bunbury Natural Gas Pipeline Access Arrangement

Corrigenda to Draft Decision

The Economic Regulation Authority today published a corrected version of the draft decision on proposed revisions to the access arrangement for the Dampier to Bunbury Natural Gas Pipeline (DBNGP) issued on 14 March 2011.

The corrected version of the draft decision incorporates the correction as detailed in the corrigenda below. The corrections are of a typographical nature and do not materially alter the Authority's draft decision.

The Authority has accordingly issued the following corrigenda to the draft decision:

• Paragraph 958, Table 77 for the T1 reference service: Replace the values for "Capacity (TJ/d)", "Throughput (TJ/d)" and "Average load factor" for 2012, 2013, 2014 and 2015 with values shown in the "Summary of the Demand forecasts applied by the Authority in determining the Reference Tariffs" (Draft Decision, Appendix 5, page 107).

The corrected Table 77 is attached to this notice.

A copy of the corrected draft decision is available on the Authority's website.

For further information contact:

General Enquiries

Rasmus Moerch A/Assistant Director Gas Ph: 61 8 9213 1900 Fax: 61 8 9213 1999

Media Enquiries

Greg Watkinson Chief Executive Officer Ph: 61 8 9213 1900 Fax: 61 8 9213 1999

LYNDON ROWE CHAIRMAN

5 May 2011

Corrigenda for the Draft Decision: Dampier to Bunbury Natural Gas Pipeline Access Arrangement

Replace the Table 77 in paragraph 958 with the following:

Summary of demand forecasts applied by the Authority in determination of amended reference tariffs

	2011	2012	2013	2014	2015
T1 reference service					
Capacity (TJ/day)	851.310	860.310	860.310	860.310	860.310
Throughput (TJ/day)	703.074	718.817	719.717	725.846	732.521
Average load factor	0.826	0.836	0.837	0.844	0.851
P1 reference service					
Capacity (TJ/day)	215.380	215.380	215.380	215.380	215.380
Throughput (TJ/day)	191.458	189.708	189.708	189.708	189.708
Average load factor	0.889	0.881	0.881	0.881	0.881
B1 reference service					
Capacity (TJ/day)	130.047	130.047	130.047	130.047	130.047
Throughput (TJ/day)	112.267	112.267	112.267	112.267	112.267
Average load factor	0.863	0.863	0.863	0.863	0.863